

Rain Bird® 752 Series

Full / Part Circle Golf Rotors

Specifications

Radius:

- 19' - 84' (5.8 m - 25.6 m)

Flow Rate:

- 6.7 to 47 gpm (0.42 to 2.97 l/s);
(1.51 to 10.68 m³/h)

Arc:

- Full-circle 360°, Adjustable 30° to 345°

Models:

- E: Electric
- IC: Integrated Control
- B: Block with Seal-A-Matic™ device

Maximum Inlet Pressure:

- Models E and IC: 150 psi (10.3 bars)
- Model B: 100 psi (6.9 bars)

Pressure Regulation Range:

- Models E, IC: 60 to 100 psi (4.1 to 6.9 bars)

Factory Pressure Settings:

- Models E and IC available in 70 and 80 psi (4.8 and 5.5 bars)

Dimensions:

- **Body Height:**
 - Models E, IC: 12.0" (30.5 cm)
 - Model B: 9.6" (24.5 cm)
- **Pop-Up Height to Mid-Nozzle:** 2.6" (6.6 cm)
- **Top Diameter:**
 - Models E, IC: 6.25" (15.9 cm)
 - Model B: 4.25" (10.8 cm)

RAPID-ADJUST TECHNOLOGY

Make easy arc adjustments with the turn of a screw. MemoryArc® feature retains two part-circle arc settings, so you can shift between full- and part-circle operation in seconds.



Step 1: Set primary rotor arc.



Step 2: Turn the Full/Part Adjustment Screw for full-circle operation.



Step 3: Turn the rotor to either Arc A or Arc B setting, then set to part-circle. No need to reset the arc when changing between full- and part-circle settings.



Nozzle Trajectory:

- **Standard:** 25°
 - #18 Nozzle: 15°
- **Wind Tolerant:** 12°
- **Low Angle:** 15°

Inlet Threads:

- Models E, IC: 1.25" (32mm) ACME female thread
- Model B: 1" (25mm) ACME female thread

Holdback:

- **Block:** 17' (5.2m) elevation

Rotation Time:

- 180° in ≤ 90 seconds; 80 seconds nominally

Maximum Stream Height:

- **Standard:** 17' (5.2m)
- **Wind Tolerant:** 10' (3.1m)
- **Low Angle:** 12' (3.7m)

Solenoid:

- 24 VAC solenoid power requirement: 0.41 amp inrush current (9.8 VA); 60 Hz: 0.25 amp holding current (6.0 VA); 50 Hz: 0.32 amp holding current (7.7 VA)

Surge Resistance:

- 25kV standard on electric models

Top-Serviceable Rock Screen™ and Replaceable Valve Seat:

- Models E, IC

Special Features:

- Self-Adjusting Stator
- Optional Sod Cup Kit (E & IC Only)



How To Specify

A	752	XX	XX	XX
Thread Type	Model	Body/ Valve	Pressure Regulator	Nozzle*
ACME	752	E	70 (4.8)	18, 20, 22, 24,
		IC	80 (5.5)	26, 28, 32, 36,
		B		40, 44, 48, 50

Descriptive text for understanding only!

Model number would look like A752IC8036 when a customer orders the IC version with a #36 nozzle at a case pressure of 80 PSI

* Nozzles up to 26 require a low-flow valve, and 28+ require a high-flow valve



U.S. Performance Data

Dual Spreader™ Nozzles with Standard Nozzle Housing

	Base Pressure (psi)	50			60			70			80			90			100		
		Radius (ft)	LA (ft)	Flow (gpm)	Radius (ft)	LA (ft)	Flow (gpm)	Radius (ft)	LA (ft)	Flow (gpm)	Radius (ft)	LA (ft)	Flow (gpm)	Radius (ft)	LA (ft)	Flow (gpm)	Radius (ft)	LA (ft)	Flow (gpm)
Low Flow Valve Required	#18 - Beige	—	—	—	—	—	—	30	—	6.8	31	—	7.2	32	—	7.5	34	—	7.8
	#20 - Gray	—	—	—	—	—	—	37	34	8.4	38	35	9.1	39	36	9.5	40	37	10.0
	#22 - Red	41	38	8.8	43	40	9.7	44	41	10.2	44	42	10.8	44	42	11.5	44	43	12.0
	#24 - Plum	46	42	8.3	47	43	8.9	47	44	9.6	48	44	10.2	48	45	10.8	48	46	11.4
	#26 - Lt. Green	50	46	9.5	50	45	10.1	51	47	10.9	51	49	11.6	52	49	12.3	53	50	12.8
High Flow Valve Required	#28 - White	54	51	14.9	56	54	16.4	58	56	17.6	58	57	18.8	57	58	20.2	59	57	21.4
	#32 - Blue	62	54	17.1	62	56	19.0	63	59	20.3	63	61	21.8	67	61	22.9	67	61	24.0
	#36 - Yellow	64	59	19.5	65	62	21.3	66	64	23.2	68	65	24.7	68	66	26.2	69	68	27.2
	#40 - Orange	63	63	22.3	65	64	24.0	67	66	26.3	68	67	27.9	69	68	29.7	69	68	31.1
	#44 - Green	—	—	—	67	66	26.9	69	68	28.6	71	70	30.6	71	71	32.5	73	71	34.0
	#48 - Black	—	—	—	—	—	—	76	—	31.5	76	—	34.0	76	—	35.8	75	—	38.5
	#50 - Dk. Brown	—	—	—	—	—	—	79	—	39.4	81	—	41.9	82	—	44.7	84	—	47.0

* Nozzles up to 26 require a low-flow valve, and 28+ require a high-flow valve

Metric Performance Data

Dual Spreader™ Nozzles with Standard Nozzle Housing

	Base Pressure (bar)	3.4				4.1				4.8				5.5				6.2				6.9			
		Radius (m)	LA (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	LA (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	LA (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	LA (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	LA (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	LA (m)	Flow (m³/h)	Flow (l/s)
Low Flow Valve Required	#18 - Beige	—	—	—	—	—	—	—	—	9.1	—	1.54	0.43	9.5	—	1.63	0.45	9.8	—	1.70	0.47	10.4	—	1.77	0.49
	#20 - Gray	—	—	—	—	—	—	—	—	11.3	10.4	1.92	0.53	11.6	10.7	2.06	0.57	11.9	11.0	2.15	0.60	12.2	11.3	2.27	0.63
	#22 - Red	12.5	11.6	2.00	0.56	13.1	12.2	2.19	0.61	13.4	12.5	2.32	0.64	13.4	12.8	2.45	0.68	13.4	12.8	2.60	0.72	13.4	13.1	2.73	0.76
	#24 - Plum	14.0	12.8	1.89	0.53	14.3	13.1	2.02	0.56	14.3	13.4	2.18	0.61	14.6	13.4	2.31	0.64	14.6	13.7	2.45	0.68	14.6	14.0	2.59	0.72
	#26 - Lt. Green	15.2	14.0	2.16	0.60	15.2	13.7	2.30	0.64	15.5	14.3	2.48	0.69	15.5	14.9	2.64	0.73	15.9	14.9	2.80	0.78	16.2	15.2	2.90	0.80
High Flow Valve Required	#28 - White	16.5	15.5	3.38	0.94	17.1	16.5	3.71	1.03	17.7	17.1	3.99	1.11	17.7	17.4	4.27	1.19	17.4	17.7	4.58	1.27	18.0	17.4	4.86	1.35
	#32 - Blue	18.9	16.5	3.88	1.08	18.9	17.1	4.32	1.20	19.2	18.0	4.62	1.28	19.2	18.6	4.94	1.37	20.4	18.6	5.20	1.44	20.4	18.6	5.44	1.51
	#36 - Yellow	19.5	18.0	4.44	1.23	19.8	18.9	4.84	1.35	20.1	19.5	5.27	1.47	20.7	19.8	5.61	1.56	20.7	20.1	5.96	1.65	21.0	20.7	6.18	1.72
	#40 - Orange	19.2	19.2	5.06	1.40	19.8	19.5	5.44	1.51	20.4	20.1	5.98	1.66	20.7	20.4	6.34	1.76	21.0	20.7	6.75	1.87	21.0	20.7	7.06	1.96
	#44 - Green	—	—	—	—	20.4	20.1	6.12	1.70	21.0	20.7	6.49	1.80	21.6	21.3	6.95	1.93	21.6	21.6	7.38	2.05	22.3	21.6	7.73	2.15
	#48 - Black	—	—	—	—	—	—	—	—	23.2	—	7.15	1.99	23.2	—	7.71	2.14	23.2	—	8.13	2.26	22.9	—	8.74	2.43
	#50 - Dk. Brown	—	—	—	—	—	—	—	—	24.1	—	8.94	2.48	24.7	—	9.52	2.64	25.0	—	10.16	2.82	25.6	—	10.68	2.97

* Nozzles up to 26 require a low-flow valve, and 28+ require a high-flow valve

Rain Bird Corporation
6991 E. Southpoint Road
Tucson, AZ 85756
Phone: (520) 741-6100
Fax: (520) 741-6522

Rain Bird Corporation
970 West Sierra Madre Avenue
Azusa, CA 91702
Phone: (626) 812-3400
Fax: (626) 812-3411

Rain Bird International, Inc.
1000 West Sierra Madre Ave.
Azusa, CA 91702
Phone: (626) 963-9311
Fax: (626) 852-7343

Rain Bird Technical Services
(800) RAINBIRD (1-800-724-6247)
(U.S. and Canada)

Specification Hotline
800-458-3005 (U.S. and Canada)

The Intelligent Use of Water™
www.rainbird.com